

6.5mm Hybrid

Product Technical Information

Dimension 1540 Range:	1540(L) x 230(W) x 6.5(T)mm
Pack Size 1540 Range:	2.1252m ²
Dimension 1860 Range:	1860(L) x 230(W) x 6.5(T)mm
Pack Size 1860 Range:	2.139m ²
Structure:	Rigid Core
Backing:	Penguin IXPE Pad
Click Profile:	5GI
Surface:	Realistic timber visuals
Pack Weight (1540mm):	18.5kg
Pack Weight (1860mm):	22kg
Edge:	Micro Bevel
Installation Method:	Floated with underlay
Origin:	PRC
Fire Rating:	ASISO 9239-1:2003 CHF 6.2kw/m ² , S,pled Value 7%
Environmental Rating:	A+. Green Building Council of Australia: Pass
Gree Star Design & As Built:	V1.1 - 13.1.2B & 13.2
Green Star Interiors:	V1.1 - 12.1.2B
Slip Resistance Value (SRV):	38
Slip Resistance (Classification):	P3
APP A: Wet Pendulum:	P12 (Y)
Formaldehyde Emission Rate:	ASTM D5116 0.020 mg/m ² /hr
Formaldehyde Emission Rate Limit:	≤ 0.1 mg/m ² /hr
Total VOC:	ASTM D5116 0.037mg/m ² /hr
Warranty - Domestic:	25 Years wear and Lifetime structural
Warranty - Commercial:	5 Year wear and lifetime structural