

## **Emission Test Certificate**

Monday 25th March 2019

Supplier: FloorTex (8 Whiteside Road, Clayton South, VIC, 3169, Australia)

Sample Description: Penguin Hybrid Flooring

Date Tested: February 2019 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D5116-2017 "Standard Guide for Small-Scale Environmental Chamber

Determinations of Organic Emissions from Indoor Material/Products".

Emission Data (24 hours):

Green Building Council of Australia Green Star Design & As Built v1.1 - 13.1.2B & 13.2 Green Star Interiors V1.1 - 12.1.2B	Penguin Hybrid Flooring
Total Volatile Organic Compound Emission Rate Limit:	Total Volatile Organic Compound
≤0.500 mg/m²/hr	Emission Rate: 0.020 mg/m²/hr
Formaldehyde Emission Rate Limit:	Formaldehyde Emission Rate:
≤0.1 mg/m²/hr	0.013 mg/m²/hr

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Nick Joy BSc(Hons)

Consultant

**Tuan Duong** 

B.Eng. (Chemical)

Consultant

CV190272